No one does it like **Lyou**

SMALL IN STATURE, **BIG ON RESULTS.**

Boasting the latest printing technology, smart features and a compact footprint, the imageRUNNER ADVANCE DX C3700i Series is ideally suited to mid-sized offices.

Canon imageRUNNER ADVANCE DX C3700i Series

E PERFORMANCE

Manage your projects with ease thanks to an intuitive design and advanced printing capabilities

- A3 mid-to-low-volume colour devices with two speeds.
- Large 10.1 inch WSVGA full colour touch screen designed for a user-friendly experience and intuitive operating feel
- Vivid and vibrant colour delivers a crisp, even finish.
- Optional space-saving Inner Finisher incorporates Eco Staple, Staple, and Staple On-demand functionalities.
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs.

S COST CONTROL

Streamline workflows while managing costs

- Forced Job Hold reduces paper and toner wastage.
- Ability to change print settings at the device allows for extra control over jobs.
- Blank page removal comes standard and works to reduce paper wastage.
- Track usage and control your costs utilising Canon's uniFLOW Online Express free software.

(INTEGRATION

Seamlessly integrate with key line-ofbusiness systems

- Seamlessly integrate with key line-ofbusiness systems to power your digital transformation journey.
- Personalised workflows give users the ability to take control of the way they want to manage their information so that it works best for them.
- Scan to myself and Google Drive plus other popular cloud destinations to enhance workflow efficiencies*.

SECURITY

Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance

- Security Information and Event Management (SIEM) system integration helps provide real-time insights into potential threats to the network and printers.
- Ensure data is secure with HDD encryption.
- Technology to verify that the device boot process, firmware, and applications initialise without alterations or tampering.

D MOBILITY

Canor

Workers and contractors can achieve ultimate freedom and flexibility with Expanded Mobile OS Support

- Mobile workflows are set up with built in WiFi and mobile applications to easily allow users to connect, print, scan and capture using Canon PRINT Business.
- Full support for Apple Airprint and Android Mopria Mobile Printing.
- Simple and easy mobile connectivity with in-built WiFi plus options to connect through Bluetooth and Near Field Communication (NFC).



Designed to help achieve environmental goals

- Motion sensors and sleep recovery triggers work to reduce unnecessary power consumption.
- Bio-based plastics are used throughout the machine for an environmentally friendly approach to printing performance.



MCAfee PROTECTED

DEVICE SECURITY

The imageRUNNER ADVANCE DX C3700i Series feature the ability to help verify that the device boot process, firmware, and applications initialise at startup, without any alterations or tampering by malicious third parties.

During operation, McAfee Embedded Control[™] utilises a whitelist to protect against malware and tampering of firmware and applications.**



CONFIGURATION



Inner 2 way tray

- Separates copies, prints and faxes
- Adds a second internal output tray



Inner finisher

- 2-tray, 600 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 40 sheets (80 gsm)





Utility tray

** These features are available on third generation imageRUNNER ADVANCE Gen III Series III or imageRUNNER ADVANCE DX models only. McAfee Embedded Control™ requires Unified Firmware Platform v3.9 or above.

Copy tray



Booklet Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and nonstaple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 50 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



Staple Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand
- 50 sheets (80 gsm)
- Supports optional internal and 4 hole inner punchers



imageRUNNER ADVANCE DX C3700i SPECIFICATIONS



Туре	A3 Colour Laser Multifunctional	
Core Function	Print, Copy, Scan, Send, Store and Optional Fax	
Processor	1.75 GHz Dual Core Processor	
Control Panel	10.1" TFT LCD WSVGA Colour Touch Panel	
Memory	Standard: 3.0 GB RAM	
Hard Disk Drive	Standard*: 320 GB (Available Disk Space: 250 GB) Optional: 1TB * A different initial HDD may be used.	
nterface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n	
	Optional: NFC, Bluetooth Low Energy Others: Standard: USB 2.0 x 1(Host), USB 3.0 x 1(Host), USB 2.0 x 1(Device)	
	Optional: Serial Interface, Copy Control Interface	
aper Supply Capacity (A4, 80 gsm)	Standard: 1,200 Sheets 2 x 550-sheet Cassettes, 100-sheet Multi-purpose Tray Maximum: 2,300 Sheets (with Cassette Feeding Unit-AP1)	
aper Output Capacity (A4, 80 gsm)	Standard: 250 Sheets Maximum: 3,450 Sheets (with Staple Finisher-AA1 or Booklet Finisher-AA1 and Copy Tray-J2)	
inishing Capabilities	Standard: Collate, Group With Options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Stapl Staple On-demand	
Supported Media Types	Multi-purpose Tray: Thin, Plain, Heavy", Recycled, Coated", Colour, Tracing, Bond, Transparency, Label, Pre-punched, Envelope *SRA3 is unsupported for Coated (257–300 gsm) and Heavy (257–300 gsm) baser.	
	Upper Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Envelope	
	Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Envelope* * Envelope Feeder Attachment A (standard) is required.	
Supported Media Sizes	Multi-purpose Tray:	
	Standard Size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Free Size: 98.4 x 139.7 mm to 320.0 x 457.2 mm	
	Envelopes: COM10 No.10, Monarch, DL, ISO-C5 Envelope Custom Size: 98.0 x 98.0 mm to 320.0 x 457.2 mm Upper Cassette:	
	Standard Size: A4, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm	
	Envelopes: ISO-C5 Lower Cassette:	
	Standard Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm	
	Envelopes*: COMIO No.10, Monarch, DL * Envelope Attachement A (standard) is required.	
Supported Media Weights	Multi-purpose Tray: 52 to 300 gsm*	
	* SRA3 is Unsupported for Coated (257–300 gsm) and Heavy (257–300 gsm) Paper. Upper/Lower Cassette: 52 to 220 gsm	
	Duplex: 52 to 220 gsm	
/arm-up Time	Quick Startup Mode: 4 seconds or less* * Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display. From Deep Sleep Mode: 10 seconds or less	
	From Power On: 10 seconds or less* * Time from device power on, until copy ready (not print reservation).	
imensions (W x D x H)	Standard (with Single Pass DADF): 565 x 722 x 887 mm	
istallation Space (W x D)	Basic: 978 x 1118 mm (with Single Pass DADF + right cover open + Multi-purpose Tray Extension Extended + Paper Cassette Open) Fully Configured: 1,651 x 118 mm (with Single Pass DADF + Staple Finisher-AA1/ Booklet Finisher-AA1 + Copy Tray-J2 Extension Extended + Paper Cassette Open)	
Veight	Standard (with Single Pass DADF): Approx. 80.6 kg Including Toner	
Print Specifications		
rint Speed (BW/CL)	IR-ADV DX C3730i: Up to 30 ppm (A4,A5,A5R,A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R), IR-ADV DX C3720i: Up to 20 ppm (A4,A5,A5R,A6R), Up to 15 ppm (A3),	
rint Resolution (dpi)*	Up to 20 ppm (A4R) 600 x 600, 1200 x 1200 (Half-speed)	
Laser Resolution	Standard: UFRII, PCL6	
les et Delet	Optional: Adobe® PostScript® 3™	
Virect Print Printing from Mobile and Cloud	Supported File Types: PDF, EPS, TIFF/JPEG and XPS AirPrint, Mopria, Google Cloud Print, Canon Business Print, and uniFLOW Online. A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for	
Fonts	further information. PCL Fonts: 93 Roman, 10 Bitmap Fonts, 2 OCR Fonts, Andalé Mono WT J/K/S/T*1	
	(Japanese, Korean, Simplified and Traditional Chinese), Barcode Fonts ⁺² PS fonts: 136 Roman *1 Requires Optional PCL International Font Set-A1	
Print Features	*2 Requires Optional Barcode Printing Kit-D1 Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided	
rint Features	Secured Print, Secure Watermark, Header/Foder, Page Layout, Wo-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer	
Operating System as of July,2019.	 UFRIL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, Mac OS X (10.10 or later) PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019 PS: Windows® 7/8.1/10/Server 2008 R2/Server 2008 R2/Server 2012/Server 2012 Server 2016/Server 2019 Windows® 7/8.1/10/Server 2008 X (10.10 or later) PD: Windows® 7/8.1/0, Mac OS X (10.9 or later) 	
Copy Specifications		
Copy Speed (BW and CL)	iR-ADV DX C3730i: Up to 30 ppm (A4, A5, A5R, A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R) iR-ADV DX C3720i: Up to 20 ppm (A4, A5, A5R, A6R), Up to 15 ppm (A3),	
Trat Capu Out Time (A.4, Divisio)	Up to 20 ppm (A4R)	
First-Copy-Out Time (A4, BW/CL)	Approx. 5.9/8.2 seconds or less	
Copy Resolution (dpi) /lultiple Copies	600 x 600 Up to 999 copies	
Copy Density	Automatic or Manual (9 Levels)	
Magnification	Variable Zoom: 25% to 400% (1% Increments) Preset Reduction/Enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%	
Copy Features	122%, 141%, 200%, 400% Preset R/E Ratios by Area, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Se Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Guiter, Print N	

Scan Specifications Type	Standard: Single-pass Duplexing Automatic Document Feeder* (2-sided to
ype	Standard: Single-pass Dupexing Automatic Document Feeder (2-sided to 2-sided (Automatic with DADF)) * Detect Feeder Multi Sheet Feed is Supported.
Document Feeder	Up to 200 Sheets
Paper Capacity (80 gsm) Acceptable Originals and Weights	Platen: Sheet, Book, and 3-Dimensional Objects
acceptable Originals and weights	Protect: a street, block, and a S-initiational Objects Document Feeder Media Weight: 1-sided Scanning: 38 to 220 gsm (BW, CL) 2-sided Scanning: 38 to 220 gsm (BW, CL) An acceptable weights of AGR or smaller is 50 to 220 gsm.
Supported Media Sizes	Platen Max. Scanning Size: Up to 297.0 x 431.8 mm Document Feeder Media Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R Custom Size: 70.0 x 139.7 mm to 304.8 x 431.8 mm
Scan Speed (ipm: BW/CL, A4)	1-sided Scanning: 135/135 (300 x 300 dpi, Send), 51/51 (600 x 600 dpi, Copy) 2-sided Scanning: 270/270 (300 x 300 dpi, Send), 51/51 (600 x 600 dpi, Copy)
Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
Pull Scan Spec	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/ Server 2012 R2/Server 2016
Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scar to USB Memory Key, Scan to Mobile device, Scan to cloud (uniFLOW Online)
Send Specifications	
Destination	Standard: E-mail/Internet FAX (SMTP) SMB 3.0 FTP WebDAV Mail Box Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution (dpi)	Push: Up to 600 x 600 Pull: Up to 600 x 600
Communication Protocol	File: FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV
File Format	E-mail/I-Fax: SMTP, POP3 Standard: TIEE IREG RDE (Compact Sparshable Apply policy Optimics for Work
Hie Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimise for Web PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals
Fax Specifications	
Maximum Number of Connection Lines	2
Modem Speed	Super G3: 33.6 kbps
	G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5", A5R", B4, B5" ² , B5R" Receiving: A3, B4, A4, A4R, A5R, B5, B5R "1 Sent as A4 *2 Sent as B4 Short
Fax Memory	Up to 30,000 pages (2,000 jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup Fax Features	Yes Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on Log
Store Specifications	
Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes
Advanced Box	Maximum 10,000 Pages (2,000 Jobs) Stored Communication Protocol: SMB or WebDAV Supported Client PC: Windows 8.1/10
Ashiran and Davidson Habita	Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Advanced Box Available Disc Space	Standard: 16 GB (With Option: Max. 480 GB)
Advanced Box Features	Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, Search, File Preview, Authentication Management, Open to Public, UF TX, Backup/Restore
Security Specifications	
Authentication and Access Control	Standard: User Authentication (Picure Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Departmen ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print"), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected,
	Advanced Box Access Control), Send Data Security (Setting for Requesting Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict FAX Driver Transmissions, Allow(Restrict Sending from History, SMIME Support), Document Tracking (Secure Watermark) "Requires unIFLOW Online/unIFLOW.
Network Security	Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)
	Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) "Hequires uniFLOW Online/uniFLOW. TLS 1.3, IPSec, IEEE802.1X Authentication, SNMP V3.0, Firewail Functionality (IP/ MAC Address Filtering), Dual Network Support (Wired LANWireless LAN, Wired LANWired LAN), Disabiling Unused Functions (Enabling/Disabiling Protocols/ Applications, Enabling/Disabiling Remote UI, Enabling/Disabiling Trobibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-Virus
Device Security	Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) "Requires uniFLOW Online/uniFLOW. TLS 13, IPSec. [EEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP/ MAC Address Filtering), Dual Network Support (Wired LAN/Wirede LAN), Disabiling Unused Functions (Enabling/Disabiling Protocols/ Applications, Enabling/Disabiling Bemote UI, Enabling/Disabiling USB Interface), G3 FAX Separation from LAN, USB port Separation from LAN, Prohibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception
Device Security Device Management and Auditing Environmental Specifications	Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) 1 Requires uniFLOW Online/uniFLOW. TLS 13, IPSec, IEEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP/ MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabiling Unused Functions (Enabling/Disabiling VB Interface), G3 FAX Separation from LAN, USB Port Separation from LAN, Prohibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data (VPF), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intusion Detection) Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting
Network Security Device Security Device Management and Auditing Environmental Specifications Operating Environment	Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) "Requires uniFLOW Online/uniFLOW. TLS 13, IPSec, IEEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP' MAC Address Filtering), Dual Network Support (Wired LAN/Wirels SLAN, Wired LAN/Wired LAN), Disabiling Unused Functions (Enabling/Disabiling Protocols' Applications, Enabling/Disabiling Water UI, Enabling/Disabiling USB Interface), G3 FAX Separation from LAN, USB port Separation from LAN, Prohibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lack), Standard HDD Initialise, Trusted Platform Module (IPM), Job Q conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection) Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event
Device Security Device Management and Auditing Environmental Specifications	Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, SMIME Support), Document Tracking (Secure Watermark) 1Requires uniFLOW Online/uniFLOW. TLS 13, IPSec, IEEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP/ MAC Address Filtering), Dual Network Support (Wired LANWiredes LAN, Wired LAN/Wired LAN), Disabiling Unused Functions (Enabling/Disabiling Protocols/ Applications, Enabling/Disabiling Remote UL, Enabling/Disabiling VB Interface), G3 FAX Separation from LAN, USB Port Separation from LAN, Prohibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialies, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection) Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

NPG-67 Toner BK/C/M/Y Toner MPG-67 Toner BK/C/M/Y Toner Yield (Estimated @5% NPG-67 Toner BK: 36,000 Pages Coverage) NPG-67 Toner C/M/Y: 19,000 Pages		Booklet Finisher-AA1	 (Includes the Staple Finisher-AA1 basic staple specifications) Booklet Stitch Paper Size: A3, A4R, B4 Booklet Stitch Staple Capacity: 20 Sheets (52 to 81.4 gsm) x 10 sets (including 1 cover sheet up to 256 gsm) Non Staple Folded Bunch Capacity: 3 Sheets (52 to 105 gsm) Power Source: From the Main Unit 	
		Software and Printer Mana		
Tracking and Reporting	Universal Login Manager (ULM), uniFLOW Online Express		(when the extension tray is extended) Weight: Approx. 53.0 kg	
Remote Management Tools	eMaintenance, Content Delivery System	2/3 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1)	
Scanning Software	Network ScanGear		Two or Three Holes Acceptable Punch Paper Weight: 52 to 300 gsm Acceptable Punch Paper Size:	
Optimisation Tools	Canon Driver Configuration Tool, NetSpot Device Installer			
Platform MEAP (Multifunctional Embedded Application Platform)			Two Holes: A3, A4, A4R, A5, B4, B5, B5R Three Holes: A3, A4, B4, B5	
Paper Supply Options			Power Source: From the Finisher	
Cassette Feeding Unit-AP1	Paper Capacity: 550 Sheets x 2 Cassettes (1,100 sheets) (80 gsm) Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched Paper Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom Size (105.02 v148.0 mm to 304.8 x 457.2 mm) Paper Weight: 52 to 220 gsm Power Source: From the Main Unit Dimensions (W x D x H); 555 x 615 x 248 mm	2/4 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1) Two or Four Holes Acceptable Punch Paper Weight: 52 to 300 gsm Acceptable Punch Paper Size: Two Holes: A3, A4, A4R, A5, B4, B5, B5R Four Holes: A3, A4 Power Source: From the Finisher	
	Weight: Approx. 16.0 kg	Hardware Accessories		
Output Options		Others	Utility Tray-B1	
Copy Tray-J2	Capacity (with 80 gsm paper):	Security Options		
	A4, A5R, B5, B5R: 100 Sheets A3, A4R, B4: 75 Sheets	Data Security	2.5 inch/1TB HDD-P1	
	Dimensions (W x D x H): 444 x 373 x 176 mm	System and Controller Op	tions	
	(attached to the main unit, when the extension tray is extended) Weight: 0.5 kg	Print Accessories	PS Printer Kit-BJ1, PCL International Font Set-A1	
Inner 2Way Tray-J1	Tray Capacity (with 80 gsm paper):	Barcode Printing	Barcode Printing Kit-D1	
	Upper Tray: SRA3, Å3, Å4, Å4Ř, A5, A5R, A6R, B4, B5, B5R, Custom Size (98.4 x 139.7 mm to 320.0 x 457.2 mm): 100 Sheets Lower Tray: A4, A5, A5R, A6R, B5, B5R: 250 Sheets	System Accessories	Copy Control Interface Kit-A1, Serial Interface Kit-K3, Connection Kit-A2 for Bluetooth LE, NFC Kit-E1	
	SRA3, A3, A4R, B4, Custom Size (98.4 x 139.7 to 320.0 x 457.2 mm): 100 Sheets	Fax Accessories	Super G3 FAX Board-AZ1, Super G3 2nd Line Fax Board-AU1, Remote Fax Kit-A1 IP FAX Expansion Kit-B1	
	Paper Weight: 52 to 300 gsm Dimensions (W x D x H): 426 x 407 x 76 mm	Other Options		
	Weight: 0.7 kg	Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1	
Staple Finisher-AA1	Upper Tray: A4, A5, A5R, B5: 100 Sheets SRA3, A3, A4R, A6R, B4, B5R: 50 Sheets Lower Tray: A4, A5, A5R, B5: 500 Sheets SRA3, A3, A4R, B4, B5R: 250 sheets, A6R: 30 Sheets Envelope: 10 sheets Paper Weight: 52 to 300 gsm Staple Capacity: A4, B5: 50 Sheets (52 to 90 gsm) A3, A4P, B4: 30 Sheets (52 to 90 gsm) A3, A4P, B4: 30 Sheets (52 to 90 gsm) A3, A4P, B4: 30 Sheets (52 to 90 gsm) A3, A4P, B4: 55 Sheets (52 to 90 gsm) A3, A4P, B4: 55 Sheets (52 to 90 gsm) Biologies (32 to 105 gsm) Staple On-demand: 40 Sheets (80 gsm) Dimension (W x D x H): 634 x 525 x 188 mm (when the extension tray is extended) Weight: Approx. 80 kg		Staple-PI, Staple Cartridge-Y1	
	Upper Tray: A4, A5, A5R, A5R, A5R, B5: 250 sheets SRA3, A3, A4R, B4, B57: 125 Sheets Lower Tray: A4, A5, A5R, B5: 300 Sheets A6R: 250 sheets Envelope: Monarch 30 sheets, COMI0 No.10, DL, ISO-C5: 100 sheets Paper Weight: Upper Tray: 52 to 256 gsm Lower Tray: 52 to 256 gsm Lower Tray: 52 to 256 gsm Staple Position: Corner, Double Staple Capacity: A4, B5: 50 sheets (52 to 90 gsm) A3, A4P, B4: 30 sheets (52 to 90 gsm) Eco Staple: A3, A4: 5 Sheets (52 to 64 gsm) 4 Sheets (65 to 81.4 gsm) 3 Sheets (62 to 159 gsm) Staple On-demand: 50 Sheets (90 gsm) Power Source: From the Main Unit Dimensions (W x D x H): 637 x 623 x 1016 mm (when the extension tray is extended) Weight: Approx. 30.0 kg			

 Canon Australia Pty Ltd
 1800 444 199

 Canon New Zealand Ltd
 0800 222 666

No one does it like **you**

canon.com.au/business canon.co.nz/business



